

Technical characteristics:

- Digital cycle indicator
- Forklift entry platform
- Working height of wrapping up to 2400 mm.
- Maximum load dimensions 1100 x 1000 mm.
- Maximum load weight 1500 kg.
- Turntable: 1500 mm diameter with gradual start, stop in any position and variable speed
- Voltage 230 / 380 V three-phase + neutral
- Power 0.7 kW
- Photocell support
- Motorised spool carriage
- MECATENS carriage set
- Variable speed spool carriage
- Photocell system for detecting height of load
- Various types of wrapping programmable by operator
- Reinforcement program for independent top, centre and bottom cycles.
- Automatic reinforcement program for central cycles according to height of load
- Double wrapping program; the spool carriage rises while wrapping
- Simple wrapping program; the spool carriage rises while wrapping
- 10 programs can be customised and saved
- Alarm tone for operation and anomalies



Optional equipment:

- Column 1900 / 2900 mm
- Single-phase machine
- Neck extension 500 mm / 1000 mm
- Pneumatic pressing plate 1.5 m
- Motorised pressing plate
- Motorised pre-stretching
- Manual load cover dispenser
- Adjustable demarcation kit (demarcation kit active when there is double or anti-rain wrapping)
- Front or side loading
- Rustproof